

RODURE Poster Films

Soltex
Single Sided Posters & Displays
SPM250

SOLTEX is a white, high opacity, low density polypropylene synthetic paper with a ink receptive textured film on one side primarily designed for eco-solvent inkjet printers. Its textured print receptive layer provides excellent ink absorption and scuff protection thus eliminating the need for over lamination and reducing production times. It is suitable for a large range of durable printed applications requiring resistance to tearing, water, premature breakdown or yellowing due to ultra-violet light exposure.



Quality

Economy

Performance

Premium

Product information

Composition:	Low density biaxially oriented polypropylene film + film layer
Main Applications:	Posters & banner stands skins
Features:	Good whiteness and opacity, textured print surface, tear & water resistant
Benefits:	Reliable printing, high durability & reduced production costs
Surface Treatment:	Corona & ink receptive film layer
Formulation:	UV stabilized, anti-static treated
Storage Conditions:	22°C 50 ~ 55% RH
Shelf Life:	2 years from date of manufacture

Certifications

Application

- Lightweight, durable posters

Manufacturing

- ISO9001

Weight

- 243 grams per m² ± 5%

Stock Availability

Sheet Sizes:	See sheet cutting
Roll Widths (mm):	915, 1270
Roll Lengths (mtrs):	45
Log Cutting:	Available
Standard Core:	76mm ID
Sheet Cutting:	Up to 3200mm x 1524mm

Durability

5 years

1 year

Printing

Method:	Most solvent, UV curable digital & screen print systems
Printable Sides:	One, face wound outside
Ink Suitability:	Solvent, UV cured, screen

Eco Response

Heavy Metal Free

- No

Recyclable

- No

Safety Compliance

- Reach, RoHS

Basic Physical Data

Thickness:	0.25mm
Weight:	243 gsm
Gloss Level:	Textured Matte

Thermal Data

Heat Resistance:	80°C
Cold Resistance:	5°C

RODURE Poster Films

Soltex
Single Sided Posters & Displays
SPM250



Physical Characteristics

Tearing Strength	10000 ↑ g/10mm (JIS Z 0237)
Thickness	0.25 mm (9.8 mil) ± 5%
Weight	243 grams per m ² ± 5%
Tensile Strength	7 ↑ kgs/mm ² in MD, 12 ↑ kgs/mm ² in CD.
Surface Finish	Textured satin
Opacity	75 ↑
UV Stabilized	Yes

Finishing

Cutting	✓
Welding	✗
Folding	✓
Gluing	✓
Eyeletting	✓
Stitching	✓
Laminating	✗
Bending	✓
Routing	✗
Punching	✓
Drilling	✓
Screwing	✓
V-Grooving	✗