

ROCAL Adhesive Films

Monomeric White Gloss Perm
3 Year Self Adhesive Graphics
SVO-P

ROCAL Monomeric vinyls have been engineered for a large range of wide format digitally printed mounted graphic applications using face stock weights & formulations that consistently capture and display ink effectively whilst providing short term durability & excellent resistance to shrinkage. SVO-P is a glossy opaque white film with a permanent, solvent based acrylic adhesive which can be wet applied and has a two side coated, moisture resistant & stay-flat paper liner.



Quality

Economy

▶ Performance

Premium

Product information

Composition:	Calandered PVC film, adhesive & release paper
Main Applications:	Short term permanent mounted graphics
Features:	Controlled, reliable print formulation & shrinkage, stay-flat liner
Benefits:	Reliable printing, high durability & flatness, visually appealing
Formulation:	Plasticised Monomeric Vinyl
Storage Conditions:	5~40°C & 35~75% RH
Shelf Life:	1 year from date of manufacture
Release Liner:	0.18mm, 120gsm double PE coated
Adhesive Type:	Clear permanent solvent based acrylic
Remarks:	Total weight including liner & adhesive 320gsm

Certifications

Quality & Testing

- Durability ISO 4892-3 (1000hr)

Application

- Short term adhesive graphics

Manufacturing

- ISO9001

Weight

- 320 grams per m² ± 5%

Stock Availability

Sheet Sizes:	See sheet cutting
Roll Widths (mm):	1020, 1370 & 1524
Roll Lengths (mtrs):	50 & 250
Log Cutting:	Available for 50m rolls only
Standard Core:	76mm for 50m and 152mm for 250m
Sheet Cutting:	Up to 3200mm x 1524mm

Durability

6 years

3 years

Printing

Method:	UV Offset, Screen & Digital
Printable Sides:	One, wound facing outside of roll
Ink Suitability:	UV Cured inks (Offset, Screen & Inkjet) Solvent & Latex

Eco Response

Heavy Metal Free

- No

Recyclable

- No

Safety Compliance

- RoHS

Basic Physical Data

Thickness:	305 micron
Weight:	320 grams per m ² ± 5%
Gloss Level:	Gloss

Thermal Data

Heat Resistance:	80°C
Cold Resistance:	-30°C
Shrinkage:	0.5 ↓ % (80°Cx48hrs)

ASK
US

ROCAL Adhesive Films

Monomeric White Gloss Perm
3 Year Self Adhesive Graphics
SVO-P



Physical Characteristics

Holding Power	0.3 ↓ mm (JIS Z 0237)
Ball Tack	6 ~ 12
180° Peel Adhesion	1800 ↑ g/25mm-24Hr (JIS Z 0237)
90° Release Force	40±20 g/50mm (JIS Z 0237)
Thickness	Film 100micron, Liner 180micron, Adhesive 25micron
Weight	320 grams per m ² ± 5%
Tensile Strength	2000 ↑ g/10mm (JIS Z 0237)
Elongation at Break	150 ↑ % (JIS Z 0237)
Gloss Level	80 ↑ Degree/60° Angle (ISO 2813)
Surface Finish	Gloss
UV Stabilized	Yes, to maximum concentration

Finishing

Cutting	✓
Welding	✗
Folding	✓
Gluing	✓
Eyeletting	✗
Stitching	✗
Laminating	✓
Bending	✗
Routing	✗
Punching	✓
Drilling	✓
Screwing	✓
V-Grooving	✗